DYNASTY RESOURCES LIMITED

QUARTERLY ACTIVITIES REPORT MARCH 2018

CORPORATE ACTIVITIES

Dynasty Resources Limited (Dynasty or the Company) undertook the following activities during the quarter ended 31 December 2017:

- Several projects are being evaluated for purchase or joint venture (JV) including cobalt, copper and gold.
- Results from rock chip sampling at the Ashburton cobalt project confirm anomalous cobalt in sediments.
- The North Shaw Lithium project is being evaluated for potential JV funding for the next phases of work.

EXPLORATION ACTIVITIES

ASHBURTON COBALT PROJECT

A reconnaissance trip to evaluate the potential of the region was completed during the last quarter. Results received confirm previous workers anomalous zones with anomalous samples of 368 ppm Co and 626 ppm cobalt being returned. The sampling was undertaken during traverses of the areas where anomalous results had been reported by previous explorers with 14 samples collected from various lithologies within the area. These varied from fine grained sediments to strongly ferruginous and

manganiferous material with fine textures within the iron



Figure 1 Previous work summary and current sampling

oxides possibly indicating sulphides.

The area appears to be part of a large sedimentary basin suitable for the formation of a sedimentary exhalative deposit. The presence of strong cobalt anomalism within some areas is encouraging. It may represent surface scavenging rather than primary mineralisation, but this would also support the presence of cobalt rich lithologies within the basin, an important potential source of metal for a sedimentary exhalative deposit. Figure 2 shows some of the more prospective lithologies encountered.





Figure 2 Rock chips from reconnaissance mapping: top right – ferruginous sedimentary breccia; top left - strongly manganiferous, fine grained sediment; Bottom left and right – fine iron oxides, possibly after sulphides, within fine grained sedimentary units.



The previous results were LAG samples collected by Newcrest in 1992. The work was located on an air photography base map and locations were taken from ledgers within their final annual report (WAMEX A39214) by Peak Minerals in 2009 (A84013). This digital file was verified against the original work. Locations are considered to be accurate within 100m and the assay techniques used for Cobalt were appropriate and likely accurate in the detection of anomalous samples. This program followed up the most anomalous samples with sampling of nearby outcrops. **CORPORATE ACTIVITIES**

Several projects have been examined during the quarter including cobalt, copper and gold projects. Dynasty is looking for quality exploration projects through to advanced projects nearing production.

Dynasty is currently looking at options for funding the ongoing Lithium exploration at their North Shaw project, with further exploration planned for the impending field season.

Figure 2 Project areas



Project	Lease	Commodity	Holder (if not DMA)	Locality
Atlas Iron JV $^{(1)}$	E45/2728	Iron - Fe		WA
Ashburton	E08/2915	Base Metals-Co		WA
Stanley ⁽²⁾	E69/2266	Uranium - U	Goldstone Resources Pty Ltd	WA
Hyden ⁽²⁾	E77/2040	Gold – Au	Goldstone Resources Pty Ltd	WA

MINING TENEMENTS HELD AT END OF QUARTER

⁽¹⁾ The Company has entered into an agreement with Atlas Iron in relation to the iron ore rights, with an entitlement to receive a 2% royalty from production

⁽²⁾ The Company holds a 16% interest in Goldstone Resources Pty Ltd

CHANGES IN INTERESTS IN TENEMENTS DURING QUARTER

None.

COMPETENT PERSONS STATEMENT

The information in this report that relates to exploration results and mineral resource calculations has been compiled by Mr David Jenkins, a full time employee of Terra Search Pty Ltd, geological consultants employed by Dynasty Resources Limited. Mr Jenkins is a Member of the Australian Institute of Geoscientists and has sufficient experience in the style of mineralisation and type of deposit under consideration and the activity which they are undertaking to qualify as Competent Persons as defined in the 2012 Edition of the Australasian Code for Reporting of Exploration Results ("JORC Code"). Mr Jenkins consents to the inclusion in the report of the matters based on the information in the form and context in which it appears.

CORPORATE PROFILE

Dynasty Resources Limited ABN 80 110 385 709

Directors Details

Lewis TayChairman and Managing DirectorBin WangIndependent DirectorKen CharterisNon-executive Director

Company Secretary Henry Kinstlinger

Registered Office and Principal Place of Business 83 Brisbane Street Perth WA 6000

Tel: +61 8 6316 4414 Fax: +61 8 6316 4404 Email: <u>admin@dynastyresources.com.au</u> Website: <u>www.dynastyresources.com.au</u>

Share Details

At 30 June 2017 there were 506,326,341 ordinary shares on issue.



1	ORC	2012	Table	1 -	
	UNC	2012	Table	T -	

Criteria	JORC Code explanation	Commentary
Sampling techniques	 Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling. Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used. Aspects of the determination of mineralisation that are Material to the Public Report. In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information. 	 Surface rock chip samples from outcropping lithologies Selected samples were taken of prospective lithologies.
Drilling techniques	 Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc). 	Not Applicable
Drill sample recovery	 Method of recording and assessing core and chip sample recoveries and results assessed. Measures taken to maximise sample recovery and ensure representative nature of the samples. Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material. 	Not Applicable
Logging	 Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies. Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography. The total length and percentage of the relevant intersections logged. 	Lithological observation made
Sub-sampling techniques and sample preparation	 If core, whether cut or sawn and whether quarter, half or all core taken. If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry. For all sample types, the nature, quality and appropriateness of the sample preparation technique. Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples. Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling. Whether sample sizes are appropriate to the grain size of 	 Not Applicable



Criteria	JORC Code explanation	Commentary		
	the material being sampled.			
Quality of assay data and laboratory tests	 The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total. For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc. Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established. 	 Samples analysed at Labwest using an Aqua Regia Digest and ICP reading. 		
Verification of sampling and assaying	 The verification of significant intersections by either independent or alternative company personnel. The use of twinned holes. Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols. Discuss any adjustment to assay data. 	Not Applicable		
Location of data points	 Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation. Specification of the grid system used. Quality and adequacy of topographic control. 	Hand held GPS		
Data spacing and distribution	 Data spacing for reporting of Exploration Results. Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied. Whether sample compositing has been applied. 	Selected samples from outcrop		
Orientation of data in relation to geological structure	 Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type. If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material. 	Not Applicable		
Sample security	• The measures taken to ensure sample security.	Samples delivered to laboratory in person		
Audits or reviews	• The results of any audits or reviews of sampling techniques and data.	Not required		

JORC 2012 Table 2 - reporting of exploration results

Criteria	JORC Code explanation	Commentary			
Mineral tenement and land tenure status	 Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings. The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area. 	E08/2915 - granted tenement in good standing.			



Criteria	JORC Code explanation	Commentar
Exploration done by other parties.	• Acknowledgment and appraisal of exploration by other parties.	 Previous work by CRA and Newcrest has been collated by previous explorer Peak Minera in 2009 (A84013). The LAG sampling was collated from surface work completed by Newcrest in 1992 (A39214)
Geology	Deposit type, geological setting and style of mineralisation.	Targeting sediment hosted bas metal mineralisation
Drill hole Information	• A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all	Historical data from digital files current data from handheld GPS.
	Material drill holes:	•
	 easting and northing of the drill hole collar 	
	elevation or RL (Reduced Level - elevation above sea level in metres) of the drill hole collar • dip and azimuth of the hole	
	down hole length and interception depth hole length.	
	• If the exclusion of this information is justified on the basis that the information is not	
	Material and this exclusion does not detract from the understanding of the report, the	
	Competent Person should clearly explain why this is the case.	
Data aggregation methods	In reporting Exploration Results, weighting averaging techniques, maximum and/or	Not Applicable
memous	minimum grade truncations (eg cutting of high grades) and cut-off grades are usually	
	Material and should be stated.	
	Where aggregate intercepts incorporate short lengths of high grade results and longer lengths	
	of low grade results, the procedure used for such aggregation should be stated and some	
	typical examples of such aggregations should be shown in detail.	
	• The assumptions used for any reporting of metal equivalent values should be clearly stated.	
Relationship between mineralisation	These relationships are particularly important in the reporting of Exploration Results.	Not Applicable
widths and intercept lengths	• If the geometry of the mineralisation with respect to the drill hole angle is known, its nature	
	should be reported.	
	• If it is not known and only the down hole lengths are reported, there should be a clear	
	statement to this effect (eg 'down hole length, true width not known').	



	NAME	MGA_E	MGA_N	Ag	As	Au	Со	Cu	Mn	S	Fe	Zn	Zr	Desc
	C4005	577219.1	7366995	0.09	59.1	< 0.5	23.5	186	1400	345	330000	424	11	Ferruginous Siltstone - Silica
	C4006	577383.9	7367294	< 0.01	3.5	< 0.5	32.4	68.2	1580	< 50	48800	153	43	Black Shale
\bigcirc	C4007	575694.7	7367558	0.04	2.4	< 0.5	626	310	66700	228	28000	195	5	Manganiferous qtz vein in shale and Sandstone
(15)	C4008	575241.6	7367574	0.14	59.2	< 0.5	7.6	84.3	830	63	165000	199	29	ferruginous Siltstone
$\widetilde{\mathbb{O}}$	C4009	575192.3	7367550	0.02	15.3	< 0.5	1.4	30.8	74	162	46400	44.3	21	Shale
	C4010	575079.8	7367573	0.21	29.1	< 0.5	12.2	63.4	594	227	333000	218	10	Siltstone
(T)	C4011	577211.9	7370038	0.02	22.7	< 0.5	16.1	65.4	547	178	367000	297	9	Sandstone, Fine grained
	C4012	577493.2	7370565	0.09	12.8	< 0.5	26.8	124	389	485	221000	318	5	Sandstone, Ferruginous
\bigcirc	C4013	577255.8	7372782	0.02	91.3	0.5	30.6	52.5	1690	282	315000	59.6	6	manganiferous shale
	C4014	577258.8	7372756	0.01	2.3	2.3	2.4	12.3	152	< 50	17300	7.5	< 1	Chert
	C4015	577272.2	7372739	0.3	458	3	368	188	117000	2140	414000	372	2	Bx manganiferous rock
\bigcirc	C4016	577272.9	7372735	0.33	55.2	1.2	92.8	160	22800	258	223000	69.3	4	Ferruginous Sandstone
	C4017	576996.4	7372766	0.04	31.3	< 0.5	17.9	225	575	1590	257000	245	3	Ferruginous sandstone
	C4018	576689.5	7374029	0.04	1.4	2.5	19.4	78.1	579	< 50	47300	126	26	Shale